



DRYSTAR™ 5300

Imager

Tabletop, next-to-application imager for decentralized workflow

- Direct Digital Imaging technology
- A decentralized hardcopy solution
- Easy daylight loading

> **DRYSTAR 5300 IS A LARGE MEDIA SIZE, DIRECT DIGITAL™ IMAGER.**

Next-to-application imaging for decentralized applications

The unit's small footprint means that convenient next-to-application installation is possible in even the most space-restricted environments. The imager of choice for decentralized applications, DRYSTAR 5300's freedom of placement makes it the perfect match for many modalities. With the low investment and running cost of this imager, equipping every department with its own imaging solution becomes a reality.

DRYSTAR 5300

Imager



Durable and reliable by design



Convenient next-to-application imaging



Excellent reliability, minimum maintenance

DRYSTAR 5300 offers all the benefits of Direct Digital Imaging. This solid-state technology avoids the use of complex optical components, making the imager reliable and durable by design. Moreover, DRYSTAR 5300 is ecological and user-friendly. No more wet processing, no darkroom, no complicated adjustments or cleaning procedures. Environmentally harmful chemicals, waste handling and disposal costs are things of the past.

Easy connectivity for maximum flexibility

DRYSTAR 5300 is a DICOM-native imager, which makes network connectivity easy. For point-to-point connection with non-DICOM modalities, DRYSTAR 5300 can be used with Agfa's LINX Paxport™.

A total, one-stop imaging solution

Through its intelligent matching of Direct Digital Imaging technology, media and imager, DRYSTAR 5300 is designed to stand at the heart of Agfa's integrated solutions. Combined with state-of-the-art DRYSTAR DT2 media, diagnostic quality grayscale hardcopies of the highest standard are delivered time after time. Because it is heat-sensitive rather than light-sensitive, DT2 brings the added convenience of daylight loading. For the DRYSTAR 5300, DRYSTAR DT2 is available in 2 media sizes: 11 x 14" and 14 x 17".

TECHNICAL SPECIFICATIONS

GENERAL

Dimensions

- 70 x 80 x 35 cm (W x D x H)
(27.5 x 31.5 x 13.8 inch)

Weight (without film)

- 55 kg/121 lb

Power requirements

- Auto ranging 100 - 240 V: 50/60 Hz

Power consumption

- Printing: 250 Watt
- Peak: 530 Watt
- Standby: 70 Watt

Capacity of supply tray

- 100 sheets

Operating conditions

- Temperature: 15 -30 °C (59 - 86 °F)
- Humidity: 10 - 80% RH, non-condensing

Storage/Shipping conditions

- Temperature: -25 to +55 °C (-11 to 131 °F)
-40 to +70 °C for transport (-40 to 158 °F)
- Humidity: 10 - 95% RH, non-condensing.

Heat dissipation

- Standby power: 70 Watt
- Average printing power: 250 Watt
- Peak power: 530 Watt

Safety

- IEC 601-1
- UL 2601
- CSA 222, Nr. 601.1 - M90
- VDE 0750
- DOH
- TÜV

PERFORMANCE

Throughput

- 11 x 14 inch: 86 sheets/hour
- 14 x 17 inch: 63 sheets/hour
- Access time first sheet approximately 77 sec.
(14 x 17" - 12-bits)

Addressable print area

- 14 x 17 inch: 4352 x 5298 pixels
- 11 x 14 inch: 3418 x 4352 pixels

Printing resolution

- Geometrical: 320 ppi
- Contrast: 12 bits contrast resolution

MEDIA

Types

- DRYSTAR DT2 B: blue base
- DRYSTAR DT2 C: clear base

Sizes

- Sizes: 11 x 14 inch and 14 x 17 inch
- 1 size on-line

Agfa, the Agfa rhombus, Point of Knowledge, See More. Do More and DRYSTAR are trademarks of Agfa Gevaert N.V., Belgium or its affiliates. All other trademarks are held by their respective owners and are used in an editorial fashion with no intention of infringement.

The data in this publication are for illustration purposes only and do not necessarily represent standards or specifications which must be met by Agfa. All information contained herein is intended for guidance purposes only, and characteristics of the products described in this publication can be changed at any time without notice.

Products may not be available for your local area. Please contact your local sales representative for availability information.

Agfa diligently strives to provide as accurate information as possible, but shall not be responsible for any typographical error.

Agfa-Gevaert N.V. has been awarded the ISO 9001 certificate by Lloyd's Register Quality Assurance. The business group HealthCare has been awarded the ISO 13485 certificate for design, development and production of imaging and communication solutions for healthcare applications.

© Copyright 2004 Agfa-Gevaert N.V.
All rights reserved



Printed in Belgium
Published by Agfa-Gevaert N.V.
B-2640 Mortsel - Belgium
NF6HD GB 00200409



| see more | do more |